COMMON MOBILITY MANAGEMENT PROTOCOL FOR MULTIMEDIA APPLICATIONS, SYSTEMS AND SERVICES

Radhika R. Roy

- [01] This application claims priority to United States provisional application Serial No.
 - 60/286,305, filed April 25, 2001 and is related by subject matter to concurrently filed U.S. patent application Serial No. (Attorney docket no. 2001-0236), both by the same inventor.

TECHNICAL FIELD

[02] This invention relates to the telecommunications field including both circuitswitched and packet-switched architectures in which mobile terminals are capable of supporting plural different multimedia applications including instant messaging, H.323 mobility and global mobility applications among others and provides a common protocol for such multimedia applications, systems and services to support terminal mobility.

BACKGROUND OF INVENTION

[03] Today's telecommunications consumer has a variety of wireless and/or wired communications devices to choose from and multimedia applications for these devices. Some of the devices include and are not limited to the following list: notebook, laptop and larger personal computers, palm-size personal computers, wireless paging devices, pocket messaging devices, cellular telephones, World Wide Web access devices as small as palm-size to laptop-size devices and cordless telephones. One or more multimedia applications can run on these devices and most, if not all of these devices may be portable or mobile. That is, the user can change location and connect in a new location either via wired line or coaxial cable at a telecommunications or coaxial cable jack (optical fiber soon to come) of wireless local area networks or wire-line networks with number portability like 800-number free-phone or wireless connection to ground-based antenna or to orbiting satellites over channels from the lower to higher (lightwave/free-space optical) frequencies of the radio frequency spectrum. Yet,

despite the differences in media used to communicate and between multimedia applications, each device commonly communicates at least where it is, its identity (and, often, who is using it) and what it wants to do to some receiving functional entity in each of these applications and supporting protocols. The multimedia architectures on which these applications run include and are not limited to wireless LAN, wireless WAN, instant messaging networks, IP web searching networks and related services, IP telephony and switched telephony (voice and video) networks, both fixed and wireless among others. Today's consumer may take their wireless cell phone to Europe or Japan from the United States and expect full connectivity for multimedia applications, fly on a plane and expect to download a movie for watching on their personal computer, take an Internet voice/video or conventional switched circuit telephone call wherever they are, search the World Wide Web and transmit and receive instantaneous messages and associated documents or data as they walk, fly on a plane, travel in an automobile or on a boat or ride on a train.

- [04] Each of the applications that play on these mobile devices have developed differently with a different messaging protocol and different addressing schemes. It is well recognized, for example, that a mobile user of such devices, today, may have as many addresses and passwords as to be almost boundless, only limited by the imagination: one's telephone number, office telephone number, office e-mail address, home e-mail address, cell phone telephone number, pager number and so on with each connection often requiring their own personal identification number or other security access code. Some of the protocols developed on an international basis include, but are not limited to H.324 POTS video-conferencing, H.323 mobility protocol, H.320 ISDN video-conferencing and S.I.P. (Session Initiated Protocol), Presence/Instant Messaging (PIM) protocol, IMT 2000 among others too numerous to mention.
- [05] In my prior U.S. Patent Application Serial Numbers 09/642,142; 09/642,279, 09/642,298 filed August 18, 2000 and Serial Number 09/825,304 filed April 4, 2001, a real-time mobility protocol, architecture and intelligent signaling scheme

are introduced for real-time applications as well as functional elements introduced for interworking among protocols, all of which should be deemed to be incorporated by reference as to their entire subject matter.

[06] Nevertheless, there are many mobile multimedia applications, as listed above, which may run independently and, permitted to develop unchecked, will cause to be built an immense infrastructure over time that can jeopardize the efficiency and speed of operation of the applications themselves. Many of the devices mentioned above are being developed to perform multiple applications and support multiple, different protocols. The manufacturers of such devices and supporting network equipment have competing interests with the managers of global networks in supporting terminal/device mobility, the former being desirous of building equipment and software for the complex architecture and the network being desirous of providing efficient speedy communications services in all mobile applications. Consequently, there is a need for a common mobility management protocol and functionality to handle the several existent, different multimedia applications.

SUMMARY OF THE INVENTION

[07] In my co-pending, concurrently filed U.S. Patent Application Serial No. (Attorney Docket No. IDS 2001-0236), entitled "Framework for Extensions of Multimedia Applications, Systems and Services to Support Terminal Mobility," incorporated herein by reference as to its entire contents, there is described a framework for a common mobility management protocol. It is demonstrated that each mobility application may have its own protocol and what will be referred to in the present application as multimedia application functional entities (MAFE) which may or may not be extended for terminal mobility among applications. The problems of extending such applications for mobility management are overcome by the principles of the present invention, a common mobility management protocol for present and future multimedia applications. A common mobility management protocol for different multimedia applications including but not limited to such multimedia applications as H.323, Presence/Instant messaging

and global mobility applications comprises an address template for defining a set of address identifiers and profile information for completing an attempted communication to an identified address and descriptors for carrying the address information. MAFE's exchange messages with mobility management functional entities (MMFE's), for example, a home location function (HLF), a visitor location function (VLF) and an authentication function (AuF), and these MMFE's exchange messages between and among themselves using the common mobility management protocol of the present invention in any of a centralized or distributed architecture.

BRIEF DESCRIPTION OF THE DRAWINGS

- [08] Figure 1 is a simplified depiction of a given multimedia application having a plurality of multimedia application functional entities, a mobile terminal and a gateway in relation to an architecture comprising a plurality of mobility management functional entities showing reference points A-F in which messaging is accomplished utilizing a common mobility management protocol according to the present invention.
- [09] Figure 2 is a simplified depiction of two, for example, two different multimedia applications communicating with a centralized home location function architecture 250 and in turn with first and second interworking functions according to the present invention showing all reference points A-F as shown in Figure 1.
- [10] Figure 3 is a simplified depiction of a distributive architecture 350 where plural home location functions communicate with plural interworking functions and a new reference point G is shown for signaling between home location functions.
- [11] Figure 4 shows steps of a location update procedure for a mobile terminal moving within a single logical boundary.

- [12] Figure 5 shows steps of a location update procedure for a mobile terminal undergoing an inter-logical boundary location change.
- [13] Figure 6 shows steps of an unregistration initiated by a mobile terminal (MT).
- [14] Figure 7 shows steps of an unregistration initiated by a multimedia application functional entity (MAFE), for example, a gatekeeper or border element in H.323.
- [15] Figure 8 shows steps of an unregistration initiated by a mobility management functional entity (MMFE), for example, a home location function.
- [16] Figure 9 shows steps of call establishment in an intra-logical boundary terminal move.
- [17] Figure 10 shows steps of call establishment in an inter-logical boundary terminal move.

DETAILED DESCRIPTION OF THE INVENTION

[18] My patent application entitled, "Framework for Extensions of Multimedia Applications, Systems and Services to Support Terminal Mobility," filed concurrently herewith and incorporated herein by reference as to its entire contents, describes that all multimedia applications (MA) have or will have multimedia application functional entities (MAFEs) [for example, gatekeepers (GKs) and border elements (BEs) in H.323] for communications with corresponding mobile terminals (MTs) that invoke the multimedia applications such as mobile terminal 110-1 of Figure 1. As explained in the BACKGROUND OF THE INVENTION section, a mobile terminal 110-1 may be without limitation any terminal that may be moved from one location to another and communicate with a network by a wired and/or a wireless link. A mobile terminal of one type, such as a personal computer, may communicate with a network server or may communicate with another fixed or mobile terminal of another type such as a POTS telephone or a paging device. Also, multimedia

applications 100-1 to 100-n mentioned below are mentioned by way of example, and it should be clear that other multimedia applications, either existent such as H.324 POTS videoconferencing or applications developed in the future are contemplated within the scope of the present invention. Each multimedia application (MA) 100-1 will use its own communications protocol between the mobile terminal (MT) 110-1 and the MAFE 115 (of which three are shown). Databases/servers that will be used for value-added mobility services residing behind the MAFE 115 are generally referred to as the home location function (HLF) 180, visitor location function (VLF) 170, and authentication function (AuF) 160. The HLF, VLF, and AuF are called mobility management functional entities (MMFEs) and utilize a common mobility management protocol according to the present invention. In the present application, a common mobility management protocol that will be used by all multimedia applications is discussed in detail and is a focus of the present invention.

Features and Capabilities of a Common Mobility Management Protocol

[19] All multimedia applications/systems that need mobility support for communications among the HLF/VLF/AuF databases will require the following features:

Terminal, Functional, and Logical Entity Profile:

- [20] There are defined below a number of common concepts that are assumed to be shared among multimedia applications.
- [21] User Identification (Alias Address): Permanent user identity (E.212 international mobile user identity [IMUI]), international mobile subscriber identity [IMSI], temporary user identity (E.212: IMUI with short lifetime), callable user identity (E.164: international mobile directory number [IMDN], RFC 2486 [email address, UR], etc.), and others comprise known means of

identifying a particular user or providing an alias address for the user intelligible to a given application. There typically will exist for any future multimedia application a user identification (alias address).

- [22] Terminal Identification (identity and [home, visited (serving), previously visited] routing address): International mobile equipment identity (IMEI), terminal type (Q.767), H.323-ID, mobile station international ISDN number (MSISDN), mobile station routing number (MSRN), temporary mobile station identity (TMSI), local mobile terminal identity (LMTI), last known location and the initial location of the H.323 mobile terminal, etc. comprise known means of identifying a particular terminal that may be mobile intelligible to a given application. There typically will exist for any future multimedia application a terminal identification.
- [23] Zone Identification: H.323 (home, visited [serving], previously visited) zone identity and others are known means of locating and identifying a zone in which a terminal is presently resident. There typically will exist for any future multimedia application a zone identification
- [24] Domain Identification: H.323 (home, visited [serving], previously visited) domain identity, DNS domain, and others are known means of locating and identifying a domain. There typically will exist for any future multimedia application a domain identification.
- [25] Functional Entity Identification (identity and routing address): HLF identity, (home, visited [serving], previously visited) VLF identity, AuF identity, H.323 (home, visited [serving], previously visited) gatekeeper (GK) identity, H.323 (home, visited [serving], previously visited) border element (BE) identity, session initiation protocol (SIP) proxy identity, and others comprise known means of

identifying a functional entity (MAFE or MMFE). There typically will exist for any future multimedia application a functional entity identification.

Routing Addressing Format:

[26] E.164 – IMDN and roaming number, IP (RFC 2000) and following protocols will define a format for routing addressing.

Services Profile:

- [27] Subscription Profile: User language, roaming restrictions (defined by operator), terminal restrictions comprise known means of defining a subscription profile for a given service subscription.
- [28] Service Status: Service granted, service barring (operator determined), service granted are known means of defining a status of a given service with respect to a given subscriber.
- [29] Traffic Parameters: Commonly known traffic parameters are known according to well known traffic engineering practices.
- [30] Basic Call: A basic call is a well known end-to-end telecommunications connection.
- [31] Call Transfer: Call transfer is a well known feature whereby a call may be transferred to another subscriber or terminal.
- [32] Call Diversion: Call diversion is a well known feature whereby a call may be diverted/routed from an intended destination to another.
- [33] Call Hold: Call hold is the well known feature of placing a call on hold.

- [34] Call Waiting: Call waiting is the well known feature of announcing a call that is waiting for connection during a pending connection.
- [35] Call Parking: Call parking is the well known feature of temporarily placing a call in a call hold like state but typically a code is required to retrieve the call from another terminal.
- [36] Call Intrusion: Call intrusion is the well known feature of permitting a call to intrude on an existing call.
- [37] Calling Name Presentation: Calling name presentation is the well known feature of presenting a calling name.
- [38] Called Name Restriction: Called name restriction is the well known feature of restricting calls to a called name.
- [39] Selective Call Rejection/Acceptance: Selective Call Rejection/Acceptance is the well known feature of selectively rejecting or accepting a call typically by calling terminal address among other means of selective call rejection/acceptance.
- [40] Message Waiting: Message waiting is the well known feature of announcing the state of a message waiting at a given terminal.
- [41] Web-based Services: Web-based services comprise the collection of services available via the world-wide web.
- [42] Unified Messaging: Unified messaging, also called integrated messaging, is the known service of announcing all messages, for example, facsimile, voice, multimedia, e-mail messages and the like.
- [43] Transport Services: Transport Type (Network: circuit-switched, packet switched [IP, ATM], System: Wireless LAN, Wire-line, 2G, 3G, GSM, UMTS, ANSI-41, H.323, SIP) and Transport Capabilities (QOS criteria, routing capability, IN capability, etc.) comprise some of the known types of transport services. There will exist a transport service for a multimedia application in the future.

- [44] In light of the above, the general mobility management protocol characteristics that are required for all multimedia applications can be described as follows: Address Resolution, Routing, Location Update, and Authentication. Consequently, a common mobility management protocol utilized by all multimedia applications must provide for these characteristics.
- [45] According to the present invention, a common mobility management (hereinafter referred to as **H.management**) protocol will provide for inter-entity messaging. That is the messages will contain fields for data parameters that may be utilized to provide the above-described functional features, characteristics and capabilities.
- Referring to Figure 1, there is provided a high level architectural view of the [46] present invention shown in bold block 150 which includes Mobility Management Functional Entities (MMFE) which communicate via a common mobility management protocol according to the present invention among themselves and with Multimedia Application Functional Entities (MAFE) for each of a plurality of different multimedia applications (MA) 100-1 to 100-n of which only MA 100-1 is shown. There are shown a number of reference points A-F and dashed and solid lines and boxes representing entities and signaling among the mobility management functional entities (MMFEs): HLF, VLF, and AuF and to a Multimedia Application Functional Entity (MAFE) for a given multimedia As described in my concurrently filed patent application (MA) 100-1. application, known MA's include H.323 multimedia, global multimedia and presence/instant messaging multimedia applications by way of example among others. Not shown are H.324 POTS video-conferencing and H.320 ISDN videoconferencing applications among others too numerous to mention or not yet developed. There may be many multimedia applications, of which only one, MA 100-1, is shown.

Protocol Description (H.management)


[47] A common mobility management protocol (H.management) according to the present invention will be used by all multimedia applications/systems that need to support mobility for maintaining the communications among home location function (HLF) 180-1, visitor location function (VLF) 170-1, and authentication function (AuF) 160-1 databases/servers shown in bold dashed line box 150. Figure 1 indicates a number of reference points A-F representing signaling among the HLF, VLF, and AuF databases/servers for any given multimedia application (MA) 100-1 wherein points A, B and D represent those that will be used between multimedia application functional entities (MAFE) and the AuF, VLF and HLF using the H.management protocol of the present invention while points C, E and F represent points between AuF, VLF and HLF to provide mobility related value added services. As will be described in connection with Figures 4-10, messaging at the H.management protocol level to interface with and among MMFE's is simplified and more efficient than if mobile terminals were required to adapt to extensions of each existent application protocol with which it may interface anywhere a mobile terminal 110-1 may relocate to in the world.

The reference points can be described as follows:

- [48] A Between Multimedia Application Functional Entity (MAFE) 115-2 for a given multimedia application MA 100-1 and Authentication Function (AuF) database/server AuF of mobility management functional entity box 150.
- [49] B Between Multimedia Application Functional Entity (MAFE) 115-2 and Visitor Location Function (VLF) database/server 170-1.
- [50] C Between Authentication Function (AuF) 160-1 and Visitor Location Function (VLF) 170-1 database/servers of mobility management functional entities box 150.
- [51] D Between Multimedia Application Functional Entity (MAFE) 115-3 and Home Location Function (HLF) 180-1 database/server.

- [52] E Between Visitor Location Function (VLF) 170-1 and Home Location Server (HLF) 180-1 database/servers.
- [53] F Between Authentication Function (AuF) 160-1 and Home Location Server (HLF) 180-1 database/servers. A further reference point is not shown in Figure 1 but may be seen in Figure 3.
- [54] G Between two Home Location Server (HLF) databases/servers (not shown in Figure 1 for simplicity)
- [55] Reference points A, B, C, D, E, F, and G are the focus of the common mobility management (H.management) protocol of the present invention. MAFE's 115 and mobile terminal 110 for a given multimedia application 100-1 use their own protocol for messaging or one enhanced for working with another protocol as described in my concurrently filed patent application. If we consider a multimedia application like H.323, a MAFE can be a gatekeeper (GK) 120-1 or Similarly, all other known and future multimedia border element (BE). applications (MA) 100 can also consider their own functional entities. However, all multimedia applications 100 will be using the same common mobility management (H.management) protocol according to the present invention for messaging reference points A, B and D. For a given multimedia application 100, there can be multiple domains using a hierarchical/centralized or distributive HLF and VLF architecture as will be further discussed below. With reference to Figures 2 and 3, there can also be multiple multimedia applications (MA) sharing the same hierarchical/centralized or distributive HLF and VLF architecture 150.
- [56] The common mobility management (H.management) protocol does not mandate a specific system architecture 150 among AuF 160-1, VLF 170-1, and HLF 180-1. There can be one or multiple AuF, VLF, and HLF functional entities (only one each being shown in Figure 1) and the communications among these entities can be of any form for a single or multiple applications: Centralized/Hierarchical or Distributive.

- [57] Also, Figure 1 shows interworking function (IWF) 190. IWF 190 comprises signaling links 125 for signaling a known gateway 120-1 for a given MA 100-1. Moreover, interworking function 190 comprises links 162-1, 172-1 and 180-2 for interworking with mobility management functional entity architecture 150. Interworking function 190 is shown linked to external networks 195 which may be any other network with which a multimedia application may interwork. Consequently, it is shown that the present H.Management protocol may work in parallel or in series with any existent interworking functionality (IWF) 190 to achieve similar results in a more efficient manner.
- Figure 2 depicts an example configuration where two multimedia applications [58] (MA₁ and MA₂) are using a single HLF 180-1 in a centralized architecture. By centralized architecture is meant the utilization of one and only one home location function 180-1 in centralized architecture 250. Similar reference numerals have been used in Figure 2 to depict similar elements in Figure 1. multimedia applications 100-1 and 100-2 are shown invoked by different terminals 110-1 and 110-2 respectively. However, both applications are using the same mobility management (H.management) protocol within centralized MMFE Multimedia application 100-1 comprises terminal 110-1, architecture 250. MAFE's 115-1 to 115-3 and gateway 120-1. Multimedia application 100-2 comprises mobile terminal 110-2 MAFE's 115-4 to 115-6 and gateway 120-2. Two interworking functions are shown, IWF 190-1 and 190-2 for connection to external networks 195. While these interworking functions are shown, they may not in fact exist and the depicted centralized architecture 250 may provide equivalent functionality. The same reference points A-F are shown in Figure 2. As in Figure 1, there is no reference point G shown because there is only one home location function 180-1. The centralized architecture may, for example, be utilized for providing multimedia application terminal mobility among any two different multimedia applications within a geographical area such as a whole country or significant portion of a highly populated country.



Addressing Schemes

- [60] The addressing convention used in the common mobility management protocol (H.management) needs to interwork with the multimedia applications that will be using the mobility management protocol. For example, in H.323, email-id and partyNumber (using PublicNumber with PublicTypeOfNumber of internationalNumber) types of AliasAddress need to be supported as well as the private local numbers. Then, these numbers may be used in messages as these are understood among the AuF, VLF, and HLF functional entities due to some a priori agreements.
- [61] The alias addresses may also contain functional entities, logical boundaries, and other kinds of identifications. For example, in H.323, there can be gatekeeper (GK), border element (BE), zone, and domain identification data included in the address.

[62] Similarly, if there are other applications that need to be supported and their addressing schemes are different, those addressing formats will also be accounted for in the addressing scheme.

Protocol Operation

- [63] The mobility management (H.management) protocol according to the present invention will be using address templates and descriptors to carry the address information. The location of the AuF, VLF, and HLF databases need to be known for the protocol operation among these mobility management functional entities (MMFE). Finally, the address resolution of the mobile terminal users is a key of the protocol operation. The detailed operation of the H.management protocol is described subsequently herein in greater detail.
- It is assumed that the multimedia application functional entities (MAFEs) 115 will communicate among themselves using the respective multimedia application-specific protocols. HLFs will advertise the user identities (i.e., their addresses) in their databases to the mobility management functional entities (MMFEs) [e.g., HLFs, VLFs] and the multimedia application functional entities (MAFEs) [e.g., GKs, and BEs of H.323, or MAFEs of IMT-2000, Presence, and Instant Messaging) among other multimedia applications using the mobility management (H.management) protocol.
- [65] For example, H.323's MAFEs like GKs and BEs will be using H.225.0 RAS and Annex G protocol among themselves. However, those GKs and BEs will be using the MMFE VLF, HLF, and AuF databases for storing all the information related to the mobile terminal users to complete the calls.

Address Templates and Descriptors

[66] An address template ("template" for short) defines a set of AliasAddress identifiers and/or the services profile information to complete calls to those addresses, and the specific protocol to be used in reaching addresses in that set for the mobile users of multimedia applications that need to support mobility.

Templates are grouped together by an identifier which may be referred to as a "descriptor". Once a template is grouped by a descriptor, any change to a template under that descriptor implies a change to the descriptor "group". Template information may allow the aggregation of addressing information if the addressing scheme is arranged in some hierarchical or routable manner (for example, a given zone might handle 1303538*, meaning all telephone numbers that begin with 1303538). (Note that since "*" is a meaningful character, the template actually includes a Boolean flag, for example, a single bit, to indicate whether the address is specific or not. These examples use "*" to indicate a wild card, but the actual representation in the template is through the Boolean flag.)

Template examples include:

- [67] "For 1 555 123 4567 send Address Resolution messages (e.g., location requests (LRQs), AccessRequest) to H.323 MAFEs (e.g., gatekeeper A, border element B)"
- [68] "For 1 555 987 * send Address Resolution messages (e.g., AccessRequest) to MMFEs (e.g., VLF C)"
- [69] "For 1 555 987 * send Address Resolution messages (e.g., AccessRequest) to MMFEs (e.g., HLF A)"
- [70] "For 1 555 987 6543 send Call Setup (e.g., Setup) message to H.323 MAFEs (e.g., H.323 gateway X)"
- [71] "For *@example.org send Address Resolution messages (e.g., AccessRequest) to MMFEs (e.g., VLF E)"
- [72] "For 1 * send Address Resolution message to IMT-2000 MAFE (e.g., MAFE Z)"
- [73] "For private 31* send Address Resolution to Presence MAFE (e.g., MAFE D)"
- [74] "For 44 171 112*" doesn't exist"

[75] An MMFE or MAFE obtains templates in one of the following ways: static configuration, receiving descriptors from other MMFEs or MAFEs in response to general requests and receiving responses to specific queries.

Static Configuration

[76] An MMFE or MAFE database will maintain templates in a way for which it is responsible. These templates may be explicitly provisioned in the MMFE or MAFE, or these templates may be formed by summarizing information obtained from the functional elements within its logical boundaries (e.g., H.323 zones, H.323 domains, DNS domains/zones). An MMFE or MAFE may make this information available to other MMFEs and MAFEs via responses to requests.


Receiving Descriptors

- [77] An MMFE or MAFE may request statically configured templates from another MMFE or MAFE. The response to the request is decided by the MMFE or MAFE from which the templates are being requested.
- [78] To request a transfer, the MMFE or MAFE sends a *DescriptorRequest* message specifying the descriptors it wishes to receive. If the owning MMFE or MAFE database is able to transfer the descriptors, it responds with a *DescriptorConfirmation* message specifying all the templates according to the protocol.
- [79] The requesting MMFE or MAFE may cache a copy of a template received in this manner until a lifetime associated with the template expires, at which point the MMFE or MAFE should delete its copy of the template. If the owning MMFE or MAFE database changes its statically configured templates before their lifetime has expired, then, it shall send a *DescriptorUpdate* message to those MMFEs or MAFEs of which it is aware. An MMFE or MAFE in receipt of a *DescriptorUpdate* message should delete, add, or change all indicated templates in its cache, or should request copies of the indicated descriptors from the owner.

- [80] An HLF may indicate itself as the contact for an *AccessRequest* message even though the descriptors it receives from another MMFE or MAFE indicate that another MMFE or a MAFE is the contact.
- [81] An MMFE or MAFE may indicate in a template the requirement for an originator to receive permission to place a call into an administrative or logical boundary (e.g., zones/domains of H.323, zones/domains of DNS). When a callSpecific flag is set in a template and the message type indicates that an AccessRequest message shall be sent, the originator shall provide per-call information in the AccessRequest message. If an MMFE or MAFE receives the AccessRequest message without per-call information and there exists a policy to require per-call information, the border element or other MAFE shall reply with an AccessRejection message with a reason of needCallInformation.
- [82] An MMFE or MAFE may send a *DescriptorUpdate* message to other known MMFEs or MAFEs, or the MMFE or MAFE may multicast a *DescriptorUpdate* message. If a *DescriptorUpdate* message is multicast, the MMFE or MAFE should consider the scope of the multicast. The *DescriptorUpdate* message can contain the descriptors that have changed. Alternatively, the *DescriptorUpdate* message may indicate only the identification of the descriptors that changed, allowing the recipient to query for the new information. If a large number of descriptorUpdate messages so that a particular *DescriptorUpdate* message does not exceed the maximum transport packet size.

Receiving Response to Specific Queries


[83] An MMFE or MAFE may send an *AccessRequest* message to another MMFE or MAFE asking for the resolution of a fully qualified or partially qualified address. The *AccessRequest* is usually sent over unreliable transport (e.g., UDP), although it may be sent over reliable transport (e.g., TCP).



- [85] The destination MMFE or MAFE may also add templates to the response which it believes will be useful in the future. The addition of these templates should not make the response so large that the transport network will need to fragment it (e.g., 576 octets for IPv4 or 1200 octets for IPv6).
- [86] For example, an MMFE or MAFE which is tightly coupled with a firewall may provide two templates in its response to *AccessRequest* messages: one template with a short lifetime (of a few minutes or seconds) specifying the location to which a call setup (e.g., Setup in H.323) message should be sent, and additional templates specifying that *AccessRequest* messages should be sent to the MMFE or MAFE for other *AliasAddresses* within the administrative or logical boundary (e.g. zones/domains in H.323 or DNS) that may have different lifetimes.
- [87] An MMFE or MAFE may cache a template received in an *AccessConfirmation* until its associated lifetime expires.

Location of Databases/Servers

[88] An MMFE or MAFE may have an administered set of other border elements which it may contact for address resolution. This administered set may be defined through a set of bilateral agreements between the administrative domains and other administrative or logical boundary (e.g. zones/domains in H.323 or DNS).



[90] Other methods to locate another MMFE or MAFE may come to mind of one of ordinary skill in the art.

Resolution Procedures


- [91] When an MMFE or MAFE is asked to resolve an *AliasAddress*, it finds matching templates in its cache. If more than one template matches, appropriate templates are selected and sorted according to local policy. For example, templates may be first sorted by wildcard length (more specific templates are better), then sorted by the type of protocol specified (for example, "Send call setup [e.g., Setup in H.323]" is better than "Send *AccessRequest*"). If multiple templates satisfy the request then the MMFE or MAFE shall return all matching templates.
- [92] If the template selection procedure produces no templates marked as "Send call setup [e.g., Setup in H.323]," then the MMFE or MAFE sends an AccessRequest message with a specific destination address to the address specified in the template. When it gets an answer from the MMFE or MAFE it may store that in its cache and return to the requester the address to which to send the call setup [e.g., Setup in H.323] message.
- [93] A ServiceProfileRequest message shall be sent when an MMFE or MAFE requires information related to the mobile user's services profiles.

- [94] Messages in the Mobility Management (H.management) protocol may be sent over an unreliable transport service (e.g., UDP) or a reliable transport service (e.g., TCP) to a well-known address. On IP networks, a well-known, predtermined port identified by *port number* should be used for both TCP and UDP, unless another port has been communicated to the sender. Border elements shall listen on both TCP and UDP ports.
- [95] When messages are sent over the reliable transport service, multiple messages may be sent within the boundaries defined by the reliable transport protocol data unit (PDU) defined by TPKT as long as whole messages are sent.
- [96] When using unreliable transport service is used, request messages may be retransmitted. The default value of the retransmission timer should determined by an adaptive delay sensitive method (such as the one used by the TCP protocol). Exponential backoff shall be used for subsequent retransmissions. The number of retransmissions, for example, shall not exceed five in number. Responses preferably shall not be retransmitted
- [97] In UDP IP implementations, messages shall also be prefixed with TPKT headers, to enable multiple messages per packet. The UDP packet length field shall hold the total length of the payload, including all the messages and their TPKT headers.
- [98] When authentication, integrity, and encryption is desired for messages exchanged between border elements, the operation of IP security shall be followed, for example, as described in IETF RFC 1825 ("Security Architecture for the Internet Protocol"), including either, or both, of IETF RFC 1826 ("IP Authentication Header"), and IETF RFC 1827 ("IP Encapsulating Protocol").
- [99] Where appropriate, the procedures and constructs of H.235 shall be utilized to support application-level security. Specifically, the token formats and authentication exchanges shall be used. Tokens and crypto-tokens received in response messages should be used in a subsequent related request.

Message Definitions

[100] Each message contains a set of common fields in addition to the message-specific information. The common fields are:

[101] Field	Description
sequenceNumber	Each request or update message contains a unique sequence number. The message sent in response to a request message (a confirmation or rejection message) uses the sequence number from the request message. Retransmitted messages shall have the same sequence number.
ReplyAddress	This is the address to which to send the reply to a request message. Any request message shall include a <i>replyAddress</i> , unless the request was sent over a bi-directional connection-oriented transport (e.g. TCP). Any message other than a request message shall not include a <i>replyAddress</i> .
Version	Protocol version in use by the sender of this message
hopCount	This defines the number of border elements through which this message may propagate. When a border element receives this message and decides that the message should be forwarded on to another border element, it first decrements <i>hopCount</i> . If <i>hopCount</i> is then greater than 0, the border element inserts the new hop count value into the message to be forwarded. If <i>hopCount</i> has reached 0, the border element shall not forward the message. If the message is a request, the border element should respond with a confirmation message with any applicable information. If no information is available, the border element should respond with a rejection message.
IntegrityCheckValue	Provides improved message integrity/message authentication. The cryptographically based integrity check value is computed by the sender applying a negotiated integrity algorithm and the secret key upon the entire message. Prior to integrityCheckValue computation each byte of this field shall be set to zero. After computation, the sender puts the computed integrity check value in the integrityCheckValue field and transmits the message.
Tokens	This is some data which may be required to allow the operation. The data shall be inserted into the message if available.
cryptoTokens	Encrypted tokens



A Descriptor

[102] The *Descriptor* is not a message, but is rather a message element used to label a set of templates.

The *Descriptor* contains the following information:

[103] Field	Description
descriptorInfo	This holds a unique identifier for the descriptor and the time it was last changed (see Descriptor Information below).
templates	This is a set of templates which define the addresses this descriptor can resolve.
functionalEntityID	This is a text identifier that indicates the owner of the descriptor (i.e., the MMFE or MAFE that created this message)

[104] Descriptor information uniquely identifies the descriptor and indicates the last time the descriptor changed.

[105] Field	Description
descriptorID	This is a globally unique identifier used to identify this descriptor from among many possible descriptors.
lastChanged	This is the date and time this descriptor was last changed.

Address template

[106] The Address Template describes a set of one or more alias addresses. The *Template* is not a message, but is an element used as a building block for other

elements. The *Template* consists of other structures, which are described in further detail below.

[107] Field	Description
Pattern	This is a list of patterns (see Pattern below)
RouteInfo	This is a list of route information for this template (see Route Information below).
TimeToLive	This indicates the time, expressed in seconds, for which this template is valid.

Route Information

[108] The route information structure found in the *template* (the *routeInfo* field) contains the following:

[109] Field	Description
MessageType	This indicates the type of message to send when attempting to resolve a specific address within this template. Possibilities are sendAccessRequest, send call setup message (e.g., Setup in H.323), or nonExistent (indicates that the address does not exist).
CallSpecific	If set to TRUE, authorization is requested for each call to this route, implying that the <i>AccessRequest</i> message shall include the call information. This boolean field has meaning only when <i>messageType</i> is <i>sendAccessRequest</i> ; otherwise, <i>callSpecific</i> shall be set to FALSE.
contacts	This is contact information for the element that will accept the message as specified in the <i>messageType</i> field of <i>routeInfo</i> . The contact information may be provided as a list of possible contacts (see Contact Information description below).
Туре	This indicates the type of endpoint that can serve the call. For MAFE (e.g., gatekeeper in H.323) routed cases, this indicates the types of endpoints served by the MAFE (e.g., gatekeeper in H.323) rather than the gatekeeper itself.

Contact Information

[110] The Contact Information structure introduced above is an element of the Route Information structure (the *contacts* field).

[111] Field	Description
transportAddress	This is the address (e.g., transport address or URL) to which to send the message specified in the message Type field of the Route Information structure. Whenever possible, a transport address shall be used.
Priority	When multiple contacts are listed, the <i>priority</i> field specifies the order in which the multiple contacts should be tried. Contacts in the list can share a priority, for example if there is no preference on the order in which the contacts should be tried. A priority of 0 indicates the highest priority (first choice).
transportQoS Security	Indicates where the responsibility lies for resource reservation for the all made through this contact Security mechanism in describing order of preference to
	be used when communicating with contact.
AccessTokens	This is a set of tokens that shall be passed in the message to this contact (call setup message [e.g., Setup in H.323] or <i>AccessRequest</i>).

Pattern

[112] The Pattern structure appears in the Address Template. The *Pattern* allows specification of an alias address, a wildcarded alias address, or a range of alias addresses:

[113] Field	Description
Specific	This is a specific alias address.

Wildcard	This some hierarchical definition that represents possible expansion of the string. For E.164 numbers this expansion is possible at the end of the number; for email addresses the expansion is possible at the beginning. For example, if wildcard is "+1 303", the pattern could represent any number in the Denver area code.
Range	This is a range of addresses, including the indicated start and end of range.

Common Structures

[114] Common structures include AlternateMobileEntity, PartyInformation, CallInformation, UserInformation and Security Mode.

The AlternateMobileEntity is described as follows:

[115] Field	Description
contactAddress	This is the alternate MMFE's or MAFE's transport address (the address to which to send mobility management (H.management) protocol messages).
Priority	When multiple alternates are listed, the <i>priority</i> field specifies the order in which the multiple alternates should be tried. Alternates in the list can share a priority, for example if there is no preference on the order in which the alternates should be tried. A priority of 0 indicates the highest priority (first choice).
element <u>I</u> dentifier	This alternate border element uses this unicode string as an identifier.

[116] PartyInformation is a structure containing information about a party of the call (either source or destination).

[117] Field	Description
logicalAddress	E-mail or E.164 formatted addresses that identify the party.
domainIdentifier	An alias address identifying the AD which originated, or terminated the call. In case where multiple domains are involved

	in placing a call, then the domain that served as the call origination or termination from the sender's perspective should be stated.
transportAddress	This is the transport address of the endpoint.
endpointType	This indicates details about the endpoint type and capabilities.
userInfo	This is information regarding the user behind the call. This may include identification in e-mail or PIN number format, and possible authentication credentials.
timeZone	This is the Time zone of the party, as relevant for pricing purposes. If the originating party is a gateway, then the time zone of the gateway has to be conveyed. Described in seconds relative to UTC.

[118] CallInformation is defined as information for identifying a specific call.

[119] Field	Description
callIdentifier	This provides unique identification of the call. This shall be the callIdentifier associated with the same call as in MAFE's signaling messages (e.g., H.225.0 RAS in H.323) and call signaling (e.g., H.225.0 Q.931 in H.323) messages.
conferenceID	This provides unique identification of the conference to which the call belongs. This shall be the conferenceID associated with the same call as in MAFE's signaling messages (e.g., H.225.0 RAS in H.323) and call signaling (e.g., H.225.0 Q.931 in H.323) messages.

[120] UserInformation is information for identifying the user on any party of the call.

[121] Field	Description
userIdentifier	Uniquely identifies the user.
userAuthenticator	Encrypted tokens for secure authentication.

[122] SecurityMode is defined as a specific security profile to be used for Mobility Management (H.management) protocol.

[123] Field	Description
authentication	This indicates the authentication mechanism to be used. The authentication mechanism must be chosen from the set provided in the <i>ServiceRequest</i> message.
integrity	This indicates the integrity mechanism to be used. If present, all subsequent messages shall populate the integrityCheckValue field, in this case, the AuthenticationMode describes the way the secret keys are generated (DH exchange, or a-priori).
algorithmOID	This indicates the encryption algorithm for the security mechanism.

Description

Service Request

- [124] An MMFE or MAFE may send a ServiceRequest message to another border element to establish a service relationship. The relationship defines the security mechanisms to be used between the MMFE or MAFE and allows identification of alternate, or backup, MMFEs or MAFEs. Note that the relationship is a one-way relationship. The security negotiated between the two MMFE/MAFEs is used for requests sent by the MMFE or MAFE that sent the ServiceRequest and for responses sent by the recipient of the ServiceRequest. Session keys may be generated during the process of service relationship establishment. The keys will be valid through the lifetime of the service relationship. Tokens may be used for that purpose, as defined in H.235.
- [125] The recipient of the *ServiceRequest* may indicate alternate MMFEs or MAFEs that the sender of *ServiceRequest* may try for backup service.
- [126] An MMFE or MAFE may send a ServiceRequest message to an MMFE or MAFE with which it has an existing relationship, with the intent that the terms of the original relationship be terminated and replaced with the new terms. Service relationships may have limited time to live. An MMFE or MAFE may refresh the

relationship by sending a new ServiceRequest. ServiceRequest contains the following fields:

[127] Field	Description
elelementIdentifier	A string that identifies the BE that sends the request.
domainIdentifier	The administrative domain AD that requests the service relationship.
securityCapability	Set of security mechanisms that this border element can support.
timeToLive	The suggested lifetime in seconds for the service relationship. If not present, infinite lifetime is assumed.

Service Confirmation

[128] An MMFE or MAFE in receipt of a ServiceRequest message responds with a ServiceConfirmation message to indicate that it agrees to establish a service relationship. If the MMFE or MAFE already has a service relationship with the MMFE or MAFE that sent the ServiceRequest message, sending ServiceConfirmation indicates that the terms of the original relationship are terminated and replaced with the new terms.

[129] Field	Description
elementIdentifier	This is a string that identifies the border element.
alternates	This is a list of alternate border elements that may be contacted in the event that this border element fails to respond.
domainIdentifier	The AD that responds to the request.
securityMode	This indicates the security mechanism to be used for this service relationship. The security mechanism must be chosen from the set provided in the <i>ServiceRequest</i> message.
timeToLive	The lifetime in seconds of the service relationship as determined by the serving border element.

Service Rejection

[130] An MMFE or MAFE in receipt of a ServiceRequest message responds with a ServiceRejection message to indicate that it declines to establish a service relationship. If the MMFE or MAFE already has a service relationship with the MMFE or MAFE that sent the ServiceRequest message, sending a ServiceRejection message indicates that the proposed new terms have been rejected, but the terms of the original relationship remain.

[131] Field	Description
reason	This is the reason the border element rejected the ServiceRequest . Choices are:
	• ServiceUnavailable – This border element is not currently available for service.
	 ServiceRedirected – The list of alternate MMFEs or MAFEs should be attempted.
	 Security – This MMFE or MAFE cannot support any of the security mechanisms proposed in the ServiceRequest message.
	 Continue – indicates the subsequent ServiceRequest message be sent, in order to continue multiple stage key exchange process

 Undefined – The reason for rejecting the ServiceRequest does not match any of the other choices.

alternates

This is a list of alternate border elements that might be able to honor the *ServiceRequest*. If the *reason* is *serviceRedirected*, at least one alternate should be provided.

Service Release

[132] Either an MMFE or a MAFE in a service relationship may terminate the relationship by sending the *ServiceRelease* message.

[133] Field	Description
Reason	This is the reason this border element terminated the service relationship. Choices are:
	 OutOfService – The border element is going out of service.
	 Maintenance – The border element is being taken out of service for maintenance.
	 Terminated – The border element has decided to terminate the relationship.
	 Expired – the time-to-live for the service relationship has elapsed.
alternates	This is a list of alternate border elements that might be able to establish a service relationship.

Service Profile Request

[134] The service profile request message will contain the following informational elements:

ServiceProfileRequest ::= SEQUENCE {
trafficParameters TrafficParameters,

basicCall BasicCall, callTransfer CallTransfer, callDiversion CallDiversion, CallHold, callHold callWaiting CallWaiting, CallParking, callParking callIntrusion CallIntrusion, callingNamePresentation CallingNamePresentation, calledNameRestriction CalledNameRestriction, SelectiveCallAcceptance, selectiveCallAcceptance selectiveCallRejection SelectiveCallRejection, MessageWaiting, messageWaiting webBasedServices WebBasedServices, unifiedMessaging UnifiedMessaging, ...other services }

- [135] The detail of this message depends on the service requested.
- [136] Service Profile Confirmation and Service Profile Rejection are other messages for confirming and rejecting a service request respectively.

Descriptor

Descriptor Request Message

[137] The DescriptorRequest message allows an entity to query a border element for specific descriptors and contains the following fields:

[138] Field	Description
descriptorID	This identifies one or more particular descriptors requested by the sender of this message.

Descriptor Confirmation

[139] The DescriptorConfirmation message is a border element's positive response to a DescriptorRequest, when the border element can interpret the request and implementation rules allow information exchange.

[140] Field	Description	
descriptors	This is the <i>descriptors</i> described above.	

Descriptor Rejection Message

[141] An MMFE or MAFE can reject a descriptor request for a variety of reasons.

[142] Field	Description
Reason	This is the reason the DescriptorRequest was rejected. Choices are:
	 PacketSizeExceeded – The reply would exceed the maximum packet size, so the requester should send the request using a different transport mechanism (e.g., use TCP instead of UDP).
	 illegalID – The recipient of the DescriptorRequest has no record of the requested descriptor.
	 security – The DescriptorRequest did not meet the recipient's security requirements.
	 HopCountExceeded – The hop count reached zero and no information is available.
	 unavailable - The recipient cannot provide descriptors. Static or out-of-band provisioning method should be used.
	 noServiceRelationship – The recipient will exchange this information only after establishment of a service relationship.
	 undefined – The reason for rejecting the DescriptorRequest does not match the other choices.
descriptorID	This identifies the specific descriptor for this response.

Descriptor ID Request

[143] The DescriptorIDRequest message allows an entity to query a MMFE or MAFE for the list of descriptor identifiers within the MMFE's or MAFE's logical or administrative boundary (e.g., zone/domain of H.323 or DNS).

Descriptor ID Confirmation Message

[144] A DescriptorIDConfirmation message is a MMFE's or MAFE's positive response to the DescriptorIDRequest message. An MMFE or MAFE in receipt of a DescriptorIDConfirmation message may send the DescriptorRequest message to request transmission of the descriptors.

[145] Field	Description
descriptorInfo	This is a list of descriptor information, where each entry in the list uniquely identifies the descriptor and the time it last changed.

Descriptor ID Rejection Message

[146] A MMFE or MAFE can reject a DescriptorIDRequest for a variety of reasons.

[147] Field	Description
Reason	This indicates the reason for rejecting the request. Choices are:
	 noDescriptors – This indicates that the border element has no descriptors to report.
	 security – The DescriptorIDRequest did not meet the recipient's security requirements.
	 hopCountExceeded – The hop count reached zero and no information is available.
	 unavailable - The recipient cannot provide descriptors. Static or out-of-band provisioning

method should be used.

- NoServiceRelationship The recipient will exchange this information only after establishment of a service relationship.
- undefined The reason for rejecting the DescriptorIDRequest does not match the other choices.

Descriptor Update

[148] The DescriptorUpdate message is a MMFE's or MAFE's notification that address information has changed. A border element may also send the DescriptorUpdate message during initialization. A border element in receipt of the DescriptorUpdate may request information from the element identified in the DescriptorUpdate.

[149] Field	Description
Sender	An element in receipt of the DescriptorUpdate may send a request to this address (e.g., transport address or URL).
updateInfo	This is a list of updates. Each entry in the list provides either the descriptor or the descriptor identifier that was updated. Each entry in the list also indicates whether the descriptor was changed, added, or deleted.

Descriptor Update Acknowledgement

[150] A MMFE or MAFE should acknowledge receipt of a DescriptorUpdate message by sending the DescriptorUpdateAck message. The squence number used in the acknowledgement should be the same as the sequence number received in the DescriptorUpdate message. A border element should not acknowledge a DescriptorUpdate message that arrives over multicast.

Access Request

[151] An MMFE or MAFE can send an AccessRequest message to another MMFE or MAFE to ask for resolution of a specific alias address.

[152] Field	Description
DestinationInfo	This is the address to be resolved.
sourceInfo	This is information about the originating party of the call to which access is requested.
CallInfo	This provides identification of the particular call for which access authorization is requested. If not present, then the request is for indefinite calls to the specified destinations.
UsageSpec	This indicates the usage messages that the originating party requests the answering party to send regarding the call requested in this message. Applies only if <i>CallInfo</i> is present.

Access Confirmation

[153] An MMFE or MAFE returns in the AccessConfirmation message the information requested in the AccessRequest message.

[154] Field	Description
templates	This is a list of tempates which match the attributes of the AccessRequest.
partialResponse	If TRUE, this message contains some fraction of the available information. The entire information was not sent because it would exceed the packet size. The entire information should be retrieved using another transport type (e.g., TCP)

Access Rejection

[155] An MMFE or MAFE can reject an AccessRequest for a variety of reasons.



[156] Field	Description
Reason	This is the reasons for rejecting the request. Choices are:
	 NoMatch – The destination specified in the AccessRequest cannot be resolved.
	 PacketSizeExceeded - The reply would exceed the maximum packet size, so the requester should send the request using a different transport mechanism (e.g., use TCP instead of UDP).
	 security – The AccessRequest did not meet the recipient's security requirements.
	 HopCountExceeded – The hop count reached zero and no information is available.
	 NoServiceRelationship – The recipient will exchange this information only after establishment of a service relationship.
	 CallInfoNeeded – Specific call information was not present in the request.
	 Undefined – The reason for rejecting the AccessRequest does not match the other choices.

Request In Progress

[157] An MMFE or MAFE may return the RequestInProgress message to indicate that the time required by the MMFE or MAFE to respond to a request may exceed normal expected response intervals. The sequence number shall be the same sequence number found in the request for which this message will be sent.

[158] Field	Description
Delay	The expected length of time, expressed in milliseconds, for the border element to respond to the original request

Unknown Message Response

[159] An MMFE or MAFE in receipt of a message it does not understand should respond to the transmitter withthe UnknownMessageResponse message. The MMFE or MAFE should not use this message if some other Mobility Management message provides an appropriate response (for example, a DescriptorRejection would be the appropriate response to a DescriptorRequest with an illegal descriptor identifier).

[160] Field	Description
unknownMessage	This is the contents of the unknown message.
Reason	This is the reason the UnknownMessageResponse was used. Choices are:
	 notUnderstood – The message was not understood.
	 undefined – The reason for sending UnknownMessageResponse does not match any of the other choices.

Validation Request

[161] An MMFE or MAFE that terminates a call can send a ValidationRequest message to another border element to verify the validity of the origination of the call.

[162] Field	Description
DestinationInfo	Details about the destination of the call.
SourceInfo	This is information about the type of endpoint that originated the call.
CallInfo	This provides identification of the particular call for which access authorization is requested.
UsageSpec	If present, indicates the border element sending the message requests that it be sent usage indication regarding the validated call.





AccessTokens

Tokens received from the originator to prove access authorization for the call.

Validation Confirmation

[163] A validation confirmation message indicates that the call is validated. The requesting border element may terminate the call. The validating MMFE or MAFE may indicate aliases to terminate the call.

[164] Field	Description
DestinationInfo	Alternative parameters for the destination to be used by the recipient border element.
UsageSpec	If present, indicates the MMFE or MAFE sending the confirmation requests that it be sent usage indication regarding the validated call.

Validation Rejection

[165] A validation rejection message indicates the call is not valid. The requesting MMFE or MAFE may not complete the call.

[166] Field	Description
Reason	This is the reasons for rejecting the request. Choices are:
	 tokenNotValid – the access token supplied are not valid for the call.
	 Security – The ValidationRequest did not meet the recipient's security requirements.
	 HopCountExceeded – The hop count reached zero and no information is available.
	 MissingSourceInfo – the source information supplied was not sufficient to validate the call.
	 MissingDestInfo – the source inforation supplied was not sufficient to validate the call.

- noServiceRelationship The recipient will exchange this information only after establishment of a service relationship.
- Undefined The reason for rejecting the ValidationRequest does not match the other choices.

Authentication Request

[167] The authentication request message will contain the following information elements:

Authentication Confirmation

[168] The authentication confirmation message will contain the following information elements:

Authentication Rejection

[169] The authentication rejection message will contain the following information elements:

Mobility Management Procedures

- [170] Each multimedia application (MA) as introduced above will use its own protocol for discovering its own multimedia functional entity (MAFE) [e.g., GK and BE in H.323], that is to be used by the mobile terminal for providing services to their mobile users. After discovery of the MAFE, a mobile entity will register with the MAFE for providing mobility related services. The protocol used among the MAFEs is called herein a multimedia application protocol (e.g., H.323, H.324, IMT-2000, Presence, Instant Messaging).
- [171] For example, in H.323, a mobile H.323 terminal 110 will discover a gatekeeper (GK) using GRQ/GCF/GRJ messages. A H.323 mobile entity will then register with the GK using the RRQ/RCF/RRJ messages. Then, the mobile entity will proceed with the call establishment.

MAFE Discovery

[172] A mobile entity such as a terminal 110 of a given multimedia application will use its own internal protocol for discovery of a MAFE to provide mobility services. For example, in H.323, a mobile H.323 terminal will discover a gatekeeper (GK) using GRQ/GCF/GRJ messages. Similarly, IMT-2000, Presence, and Instant Messaging application will also do, where applicable. The discovery for each application will be protocol-specific and will be described separately for each application.

Registration with MAFE

[173] Registration with the MAFE is needed by a mobile entity to have the services. For example, in H.323, a mobile H.323 terminal will register with the GK using RRQ/RCF/RRJ messages. Similar is the case for IMT-2000, Presence, and Instant Messaging application. The detail registration procedure for each application will be addressed separately.

Location Updating in Single Logical Boundary

- [174] Each multimedia application (MA) will have its own logical boundary. The protocol used in the logical boundary is application-specific. For example, in H.323, zones and domains have been defined as the logical boundaries, and H.323 protocol is used in those zones and domains. Similar is the case for other applications. However, the mobility management (H.management) protocol is a common protocol that is used by all multimedia applications.
- [175] Figure 4 shows how location update is processed using the mobility management (H.management) protocol while the mobile terminal (MT) 110 moves in a given single logical boundary (e.g., intra-zone in H.323).
- [176] Information flows shown in steps 1-10 are self explanatory. Steps 1, 8, 9, and 10 use the application-specific protocol by the MT 110 for communicating with the MAFE 115. However, the information flows used in steps 2-7 use the mobility management (H.management) protocol. These steps 2-7 simply involve the transmission of validation request messages in sequence from a MAFE, for example, a gatekeeper or border element, via a VLF and HLF to Authentication Function (AuF) and return.

Location Updating in Multiple Logical Boundaries

[177] If an MT 110 belongs to its home logical boundary and moves to a visited logical boundary, the communications will be different and slightly more complicated. First, MT 110 needs to register with the visited MAFE. For example, in H.323,

an MT moves from its home domain to the visited domain (or from home zone to the visited zone). IMT-2000 and other multimedia applications will also have the similar situations.

[178] Information flows in Figure 5 use two protocols: Application-Specific (Steps 1, 8-9, 16) and the common Mobility Management (H.management) protocol of the present invention [Steps 2-7, 10-15, 17-20]. In this more complicated scenario than Figure 4, there are two sets of sequential message flows, steps 2-7 and 10-15 for validation request and confirmation. There is also a descriptor update process involving a previously visited VLF, steps 17-20.

Unregistration Initiated by Mobile Terminal

- [179] Figure 6 shows the unregistration initiated by a MT 110.
- [180] Steps 1 and 3 use the application-specific protocol while steps 2, 4, and 5-6 use the Mobility Management (H.management) protocol. Steps 2, 4 and 5-6 provide descriptor database access at home location function (HLF) via VLF. An unregister confirmation need not await acknowledgement of a descriptor update. Also, a descriptor update acknowledgement from VLF to MAFE, step 5, need not await acknowledgement from the HLF, step 6.

Unregistration Initiated by the MAFE

- [181] Figure 7 shows the unregistration initiated by the MAFE (e.g., GK in H.323).
- [182] Steps 1 and 2 use the application-specific protocol while steps 3-6 use the Mobility Management (H.management) protocol. As in Figure 6, in Figure 7, an unregister confirmation need not await acknowledgement of a descriptor update. Also, a descriptor update acknowledgement from VLF to MAFE, step 5, need not await acknowledgement from the HLF, step 6.

Unregistration Initiated by the MMFE (e.g., HLF)

- [183] Figure 8 shows the unregistration initiated by the MMFE (e.g., HLF). A HLF can initiate the unregistration based on the policy of the mobility management.
- [184] Steps 4 and 6 use the application-specific protocol while steps 1-3 and 5 use the Mobility Management (H.management) protocol. When a VLF receives a descriptor update message, step 1, from an HLF, the VLF may transmit a descriptor update to a MAFE, step 2, and acknowledge the HLF, step 3, before the MAFE acknowledges, step 5, or receives an unregister confirmation from the mobile terminal, step 6.

Call Setup in Intra-Logical Boundary

- [185] An MT may move within a single boundary (or intra-logical boundary) while the call is being set up, for example, from a fixed terminal to a mobile terminal (MT) endpoint. In H.323, it can be such that a H.323 mobile user moves within its home zone known as the intra-zone movement.
- [186] Steps 1 and 6-11 use the application-specific protocol while steps 2-5 use the Mobility Management (H.management) protocol for access request of the HLF by the MAFE and access confirmation.

Call Setup in Inter-Logical Boundary

- [187] Figure 10 depicts the call establishment when a MT moves from its home logical boundary (e.g., home domain or home zone in H.323) to the visited logical boundary (e.g., visited domain or visited zone in H.323). This situation is also known as the inter-logical boundary (e.g., inter zone, inter-domain in H.323) call establishment.
- [188] Steps 1 and 8-19 use the application-specific protocol while steps 2-7 use the Mobility Management (H.management) protocol. The visited MAFE by the mobile terminal endpoint sequentially transmits an access request via the visited VLF to an HLF and once access is confirmed by the HLF, step 7, the visited

MAFE confirms the endpoint for access, step 8, and call set up to the mobile terminal endpoint proceeds, steps 9-19.

Message Syntax

[189] Mobility management (H.management) protocol message syntax contains the following:

MOBILITY MANAGEMENT MESSAGES DEFINITIONS AUTOMATIC TAGS ::= BEGIN

ServiceRequest,

ServiceConfirmation,

IMPORTS

```
Message ::= SEQUENCE
                  MobilityManagemetMessageBody,
body
                  MobilityManagemetCommonInfo
common
```

MobilityManagemetMessageBody ::= CHOICE

{

serviceRequest serviceConfirmation

ServiceRejection, serviceRejection ServiceRelease, serviceRelease ServiceProfileRequest, serviceProfileRequest ServiceProfileConfirmation, serviceProfileConfirmation ServiceProfileRejection, serviceProfileRejection DescriptorRequest, descriptorRequest descriptorConfirmation DescriptorConfirmation, DescriptorRejection, descriptorRejection descriptorIDRequest DescriptorIDRequest,

descriptor IDConfirmation Descriptor IDConfirmation, Descriptor IDRejection, descriptor IDRejection DescriptorUpdate, descriptorUpdate descriptorUpdateAck DescriptorUpdateAck,

AccessRequest, accessRequest

AccessRequestConfirmation,

accessRequestConfirmation AccessRejection, accessRejection ValidationRequest, validationRequest validationConfirmation ValidationConfirmation, validationRejection ValidationRejection, AuthenticationRequest, authentication Request authentication Confirmation AuthenticationConfirmation,

```
AuthenticationRejection
authentication Rejection
}
MobilityManagemetCommonInfo ::= SEQUENCE
sequenceNumber
                         INTEGER (0..65535),
                         MobilityManagementVersion,
version
                         INTEGER (1..255),
hopCount
                         SEQUENCE OF TransportAddress OPTIONAL, -- Must
replyAddress
                         be present in request
                         ICV OPTIONAL,
integrityCheckValue
                         SEQUENCE OF ClearToken OPTIONAL,
tokens
                         SEQUENCE OF CryptoApplicationSpecificToken
cryptoTokens
                         OPTIONAL,
                         SEQUENCE OF NonStandardParameter OPTIONAL
nonStandard
-- Mobility Management Messages
ServiceRequest ::= SEQUENCE
elementIdentifier
                         ElementIdentifier OPTIONAL,
                          AliasAddress OPTIONAL,
domainIdentifier
                          SEQUENCE OF SecurityMode OPTIONAL,
securityMode
                         INTEGER (1..4294967295) OPTIONAL,
timeToLive
...
}
SecurityMode ::= SEQUENCE
                          AuthenticationMechanism OPTIONAL,
authentication
                          IntegrityMechanism OPTIONAL,
integrity
algorithmOIDs
                          SEQUENCE OF OBJECT IDENTIFIER OPTIONAL,
}
ServiceConfirmation ::= SEQUENCE
                          ElementIdentifier,
elementIdentifier
                          AliasAddress,
domainIdentifier
                          AlternateMobileEntityInfo OPTIONAL,
alternates
                          SecurityMode OPTIONAL,
securityMode
                          INTEGER (1..4294967295) OPTIONAL,
timeToLive
```

```
}
ServiceRejection ::= SEQUENCE
reason
                           ServiceRejectionReason,
                           AlternateMobileEntityInfo OPTIONAL,
alternates
}
ServiceRejectionReason ::= CHOICE
serviceUnavailable
                           NULL,
                           NULL,
serviceRedirected
                           NULL,
security
                           NULL,
continue
undefined
                           NULL,
}
ServiceRelease ::= SEQUENCE
{
                           ServiceReleaseReason,
reason
                           AlternateMobileEntityInfo OPTIONAL,
alternates
•••
}
ServiceReleaseReason ::= CHOICE
outOfService
                           NULL,
                           NULL,
maintenance
                           NULL,
terminated
                           NULL,
expired
}
ServiceProfileRequest ::= SEQUENCE
trafficParameters
                           TrafficParameters,
basicCall
                           BasicCall,
callTransfer
                           CallTransfer,
                           CallDiversion,
callDiversion
callHold
                           CallHold,
                           CallWaiting,
callWaiting
```

CallParking, callParking CallIntrusion, callIntrusion CallingNamePresentation, callingNamePresentation CalledNameRestriction, calledNameRestriction SelectiveCallAcceptance, selectiveCallAcceptance selectiveCallRejection SelectiveCallRejection, MessageWaiting, messageWaiting webBasedServices WebBasedServices, UnifiedMessaging, unifiedMessaging } ServiceProfileConfirmation ::= SEQUENCE { } ServiceProfileRejection ::= SEQUENCE { ... } DescriptorRequest ::= SEQUENCE descriptorID SEQUENCE OF DescriptorID DescriptorConfirmation ::= SEQUENCE **SEQUENCE OF Descriptor** descriptor DescriptorRejection ::= SEQUENCE { DescriptorRejectionReason, reason DescriptorID OPTIONAL descriptorID DescriptorRejectionReason ::= CHOICE packetSizeExceeded NULL, -- use other transport type NULL, -- no descriptor for provided descriptorID illegalID NULL, -- request did not meet security requirements security hopCountExceeded NULL, noServiceRelationship NULL,

```
undefined
                          NULL
}
DescriptorIDRequest ::= SEQUENCE
}
DescriptorIDConfirmation ::= SEQUENCE
descriptorInfo
                          SEQUENCE OF DescriptorInfo
DescriptorIDRejection ::= SEQUENCE
                          DescriptorIDRejectionReason
reason
}
DescriptorIDRejectionReason ::= CHOICE
                          NULL, -- no descriptors to report
noDescriptors
                          NULL, -- request did not meet security requirements
security
hopCountExceeded
                          NULL,
                          NULL,
noServiceRelationship
                          NULL
undefined
}
DescriptorUpdate ::= SEQUENCE
{
sender
                           Alias Address,
                           SEQUENCE OF UpdateInformation,
updateInfo
                           SEQUENCE
UpdateInformation ::=
      descriptorInfo CHOICE
                          DescriptorID,
             descriptorID
             descriptor
                           Descriptor,
       updateType
                    CHOICE
```

```
added
                          NULL,
                          NULL,
             deleted
             changed
                          NULL
      },
}
DescriptorUpdateAck ::= SEQUENCE
AccessRequest ::= SEQUENCE
                          PartyInformation,
destinationInfo
                          PartyInformation OPTIONAL,
sourceInfo
                          CallInformation OPTIONAL,
callInfo
                          UsageSpecification OPTIONAL,
usageSpec
}
AccessConfirmation ::= SEQUENCE
templates
                          SEQUENCE OF AddressTemplate,
                          BOOLEAN,
partialResponse
AccessRejection ::= SEQUENCE
reason
                          AccessRejectionReason,
}
AccessRejectionReason ::= CHOICE
{
                          NULL, -- no template matched the destinationInfo
noMatch
                          NULL, -- use other transport type
packetSizeExceeded
                          NULL, -- request did not meet security requirements
security
hopCountExceeded
                          NULL,
needCallInformation
                          NULL, -- Call Information must be specified
noServiceRelationship
                          NULL,
undefined
                          NULL
ValidationRequest ::= SEQUENCE
accessToken
                          SEQUENCE OF AccessToken OPTIONAL,
```

```
destinationInfo
                          PartyInformation OPTIONAL,
sourceInfo
                          PartyInformation OPTIONAL,
callInfo
                          CallInformation,
                          ServiceSpecification OPTIONAL,
serviceSpecification
ValidationConfirmation ::= SEQUENCE
destinationInfo
                          PartyInformation OPTIONAL,
serviceSpecification
                          ServiceSpecification OPTIONAL,
ValidationRejection ::= SEQUENCE
                           ValidationRejectionReason,
reason
ValidationRejectionReason ::= CHOICE
tokenNotValid
                          NULL,
                          NULL, -- request did not meet security requirements
security
hopCountExceeded
                          NULL,
                          NULL,
missingSorceInfo
                          NULL,
missingDestInfo
noServiceRelationship
                          NULL,
                           NULL
undefined
AuthenticationRequest ::= SEQUENCE
sourceInfo
                           PartyInformation,
                           ApplicationSpecificMessage – for example tunneled RAS
tunneledMessage
                           messages in H.323
}
AuthenticationConfirmation ::= SEQUENCE
                           SEQUENCE OF EncryptionToken OPTIONAL,
encryptionToken
destinationInfo
                           PartyInformation OPTIONAL
}
AuthenticationRejection ::= SEQUENCE
                           AuthenticationRejectionReason,
reason
                           ApplicationSpecificMessage OPTIONAL,
tunneledMessage
destinationInfo
                           PartyInformation OPTIONAL,
```

```
}
EncryptionToken ::= CHOICE
                          ClearToken,
token
                          CryptoApplicationSpecificToken
cryptoToken
AuthenticationRejectionReason ::= CHOICE
                                NULL,
security
                                NULL,
hopCountExceeded
                                NULL,
missingSourceInfo
noServiceRelationship
                                NULL,
undefined
                                NULL
}
--- Structures of Common Messages
AddressTemplate ::= SEQUENCE
{
pattern
                          SEQUENCE OF Pattern,
                          SEQUENCE OF RouteInformation,
routeInfo
                          INTEGER (1..4294967295),
timeToLive
Pattern ::= CHOICE
                   Alias Address,
specific
                   AliasAddress,
wildcard
      range SEQUENCE
      {
             startOfRange PartyNumber,
             endOfRange PartyNumber
      },
}
RouteInformation ::= SEQUENCE
      messageType CHOICE
             sendAccessRequest NULL,
                                 NULL, -- specific for each application
             sendSetup
                                 NULL,
             nonExistent
```

```
},
      callSpecific
                          BOOLEAN,
      serviceSpecification ServiceSpecification OPTIONAL,
                          SEQUENCE OF ContactInformation,
      contacts
                          EndpointType OPTIONAL,
      type
                          -- must be present if messageType = sendSetup
}
ContactInformation ::= SEQUENCE
                          Alias Address,
transportAddress
                          INTEGER (0..127),
priority
                          TransportQOS OPTIONAL,
transportQoS
                          SEQUENCE OF SecurityMode OPTIONAL,
security
                          SEQUENCE OF AccessToken OPTIONAL,
accessTokens
}
Descriptor ::= SEQUENCE
descriptorInfo
                          DescriptorInfo,
                          SEQUENCE OF AddressTemplate,
templates
                          ApplicationEntityID OPTIONAL,
applicationEntityID
}
DescriptorInfo ::= SEQUENCE
descriptorID
                          DescriptorID,
lastChanged
                          GlobalTimeStamp,
•••
}
AlternateMobileEntityInfo ::= SEQUENCE
alternateMobileEntity
                          SEQUENCE OF AlternateMobileEntity,
alternateIsPermanent
                          BOOLEAN,
}
AlternateMobileEntity ::= SEQUENCE
```

```
Alias Address,
contactAddress
                           INTEGER (1..127),
priority
elementIdentifier
                           ElementIdentifier OPTIONAL,
}
AccessToken ::= CHOICE
{
                    ClearToken,
token
cryptoToken
                    CryptoApplicationSpecificToken,
}
CallInformation ::= SEQUENCE
callIdentifier
                    CallIdentifier,
conferenceID
                    ConferenceIdentifier,
}
ServiceCallStatus ::= CHOICE
{
                           NULL, -- Call has not started
preConnect
                           NULL, -- Call is in progress
callInProgress
                           NULL, -- Call ended
callEnded
}
UserInformation ::= SEQUENCE
{
userIdentifier
                           AliasAddress,
                           SEQUENCE OF CryptoApplicationSpecificToken
userAuthenticator
                           OPTIONAL,
}
PartyInformation ::= SEQUENCE
       logicalAddresses
                           SEQUENCE OF Alias Address,
       domainIdentifier
                           Alias Address OPTIONAL,
       transportAddress
                           AliasAddress OPTIONAL,
       endpointType
                           EndpointType OPTIONAL,
                           UserInformation OPTIONAL,
       userInfo
                           TimeZone OPTIONAL,
       timeZone
```

```
}
Role ::= CHOICE
                          NULL,
originator
destination
                          NULL,
nonStandardData
                          NonStandardParameter,
}
TimeZone ::= INTEGER (-43200..43200) -- number of seconds relative to UTC
                                       -- including DST if appropriate
TerminationCause ::= SEQUENCE
releaseCompleteReason
                                 ReleaseCompleteReason,
                                 INTEGER (1..65535) OPTIONAL,
causeIE
nonStandardData
                                 NonStandardParameter OPTIONAL,
}
                                 OBJECT IDENTIFIER
MobilityManagementVersion::=
                          -- shall be set to
                          -- {itu-t (0) recommendation (0) h(8) XXXXXX version (0)
1}
                   GloballyUniqueID
DescriptorID ::=
ElementIdentifier::= BMPString (SIZE(1..128))
GlobalTimeStamp ::= IA5String (SIZE(14)) -- in the form YYYYMMDDHHmmSS
                                        -- where YYYY = year, MM = month, DD =
                                        day,
                                        -- HH = hour, mm = minute, SS = second
                                        -- (for example, 19981219120000 for noon
                                        -- 19 December 1998)
```

[190] The following message elements may be similarly defined:

AuthenticationMechanism, TimeStamp, ClearToken

}

FROM H235-SECURITY-MESSAGES

[191] AliasAddress, TransportAddress, ReleaseCompleteReason, ConferenceIdentifier, CallIdentifier, CryptoMobileEntityToken, CryptoToken, EndpointType, GatekeeperIdentifier, GloballyUniqueID, NonStandardParameter, NumberDigits, PartyNumber, TransportQOS, VendorIdentifier,


IntegrityMechanism, ICV

END -- of MOBILITY MANAGEMENT MESSAGES

Relationship between Common Mobility Management Protocol and H.MMS. 1/2/3

- [192] The mobility management (**H.management**) protocol will be used as the common base protocol for mobility management by all applications.
- [193] H.MMS.1 will use the mobility management (H.management) protocol in the H.323 application-specific environment. That is, a MAFE protocol part as described above will be H.323 while the mobility management part of H.MMS.1 will be H.management.
- [194] H.MMS.2 will use the mobility management (H.management) protocol in the IMT-2000 application-specific environment. That is, a MAFE protocol part as described above will be IMT-2000 while the mobility management part of H.MMS.2 will be **H.management**.
- [195] H.MMS.3 will use the mobility management (H.management) protocol in the Presence/Instant Messaging application-specific environment. That is, a MAFE protocol part as described above will be Presence/Instant Messaging while the mobility management part of H.MMS.3 will be H.management.

Scope of Q.5/16



Conclusion

- [197] A common mobility management protocol for Q.5/16 (Mobility for Multimedia Systems/Applications and Services) has been proposed. All applications that need to support mobility management among their home location function (HLF) and visitor location function (VLF) databases/servers can use this protocol. The reference architecture, functional characteristics, features, and capabilities of the protocol along with call flows and message syntax have been described.
- [198] In this context, the scope of Q.5/16 and how H.MMS.1 (H.323 Mobility), H.MMS.2 (Global Mobility), and H.MMS.3 (Presence/Instant Messaging Mobility) can be a part of the same common mobility management protocol have also been presented.